

MSDS-4416

4x4 DVI Distributor

IMAGE



DEFINITION

- MSDS-4416 distribute four TMDS input signal up to four display devices such as a Projector, PDP, HDTV and TFT-LCD without diminution and distortion.
- This distribution support single/dual 8~16 bit and user can select input signal by press button and make sure being connected input source with led of the front panel.

SPECIFICATION

Input/Output Channel	4 Channels / 4 Channels
Pixel Clock	* Single Link : 25~165MHz * Dual Link : 25~330MHz
Data Bit	8~16 Bit
Input/Output Signal	TMDS
Input/Output Connector	DVI-I
Options	Support RS-232C
Power Consumption	100~240VAC, 50/60Hz, 1.5A
Operating Conditions	* Temperature : 0~40℃ * 80% Humidity, Non-condensing
Dimension(WXDXH)	360 X 230 X 75mm, Weight : 2.2Kg

* All specifications are subject to change without any notice.

Tel. 82-55-297-8880 / Fax. 82-55-256-7388

Address. #42-20, Palyong, Changwon, Gyeongnam, 641-847, Korea

Homepage. www.Ltdmaster.com

E-mail. sales@Ltdmaster.com / webmaster@Ltdmaster.com

Master Co., Ltd



Find Your Digital Solutions!