

MSHD-02

1x2 D-TV Distributor

IMAGE



DEFINITION

- MSHD-02 distribute inputted component signal to the two(2) output channels via RCA connector without diminution & distortion.
- It is taken High Bandwidth Video Distributor IC which is support the highest component resolution up to 1920X1080P & Dot Clock 148.5MHz.

SPECIFICATION

Input/Output Channel	1 Channel / 2 Channels
Pixel Clock	8~150MHz
Input Connector	Video(Y,Pb,Pr) : BNC
Output Connector	Video(Y,Pb,Pr) : BNC
Y Level Attenuation	Input(1.0Vp-p / Load 75ohm)±20mV : Level Control for VR
Pb, Pr Level Attenuation	Input(700mV / Load 75ohm)±10mV : Level Control for VR
Resolution	480i/p, 576i/p, 720p, 1080i/p for ATSC and DVB Format
Power Consumption	AC 100~240VAC, 50/60Hz Auto Switch
Operating Conditions	* Temperature : 0~40℃ * 80% Humidity, Non-condensing
Dimension(WXDXH)	245 X 140 X 40mm, Weight : 0.7Kg

* All specifications are subject to change without any notice.

Tel. 82-55-297-8880 / Fax. 82-55-256-7388

Address. #42-20, Palyong, Changwon, Gyeongnam, 641-847, Korea

Homepage. www.Ltdmaster.com

E-mail. sales@Ltdmaster.com / webmaster@Ltdmaster.com

Master Co., Ltd



Find Your Digital Solutions!