

# MSHD-05N (DSTAVD115X)

1x5 D-TV Distributor

## IMAGE



## DEFINITION

- MSHD-05N distribute received one(1) D-TV(Y,Pb,Pr) and audio(R,L) signal to the five(5) channels.
- It is recommended reliable test room and show room.

## SPECIFICATION

Input/Output Channel	1 Channel / 5 Channels
Pixel Clock	8~150MHz
Input Connector	Video(Y,Pb,Pr) : RCA, Audio(R,L) : RCA
Output Connector	Video(Y,Pb,Pr) : RCA, Audio(R,L) : RCA
Y Level Attenuation	Input(1.0Vp-p / Load 75ohm) $\pm$ 20mV : Level Control for VR
Pb, Pr Level Attenuation	Input(700mV / Load 75ohm) $\pm$ 10mV : Level Control for VR
Audio Bandwidth	20Hz~20KHz
Resolution	480i/p, 576i/p, 720p, 1080i/p for ATSC and DVB Format
Power Consumption	AC 100~240VAC, 50/60Hz Auto Switch
Operating Conditions	* Temperature : 0~40°C * 80% Humidity, Non-condensing
Dimension(WXDXH)	200 X 135 X 105mm, Weight : 0.8Kg

\* All specifications are subject to change without any notice.

Tel. 82-55-297-8880 / Fax. 82-55-256-7388

Address. #42-20, Palyong, Changwon, Gyeongnam, 641-847, Korea

Homepage. [www.Ltdmaster.com](http://www.Ltdmaster.com)

E-mail. [sales@Ltdmaster.com](mailto:sales@Ltdmaster.com) / [webmaster@Ltdmaster.com](mailto:webmaster@Ltdmaster.com)

Master Co., Ltd



Find Your Digital Solutions!