

MSHM-305A Plus

3x5 HDMI CEC Distributor

IMAGE



DEFINITION

- MSHM-305A Plus, HDMI Distribution Amplifier, distribute three digital video input sources to the five output channels.
- The built-in amplification function enables HDMI signal distribution without signal loss.
- The product guarantees to support full channels HDMI/HDCP compliance.
- It is also built-in CEC function according to current market request.
- User can select one(1) input source of the three and make sure connected condition with led of the front panel.

SPECIFICATION

Input/Output Channel	3 Channels / 5 Channels
Pixel Clock	25~165MHz (TMDS Clock : 25~225MHz)
Input/Output Connector	Type A Connector
HDMI Compliance	HDMI 1.3 Specification (CEC Support)
Audio Sampling Frequency	Maximum 192KHz (5 Channels)
Resolution	* VGA, SVGA, XGA, UXGA for PC * 480i/p, 720i/p, 1080i/p for HDTV
Input/Output Signal	TMDS
Options	* Supports HDCP setting * Supports EDID Mode selecting
Power Consumption	AC 100~240VAC, 50/60Hz Auto Switch
Operating Conditions	* Temperature : 0~40°C * 80% Humidity, Non-condensing
Dimension(WXDXH)	430 X 250 X 55mm, Weight : 2.7Kg

* All specifications are subject to change without any notice.

Tel. 82-55-297-8880 / Fax. 82-55-256-7388

Address. #42-20, Palyong, Changwon, Gyeongnam, 641-847, Korea

Homepage. www.Ltdmaster.com

E-mail. sales@Ltdmaster.com / webmaster@Ltdmaster.com

Master Co., Ltd



Find Your Digital Solutions!