

6X4 UD HDMI SELECTOR SWITCH

MSHM-64A



Image



Feature

MSHM-64A receive 6 of HDMI input signal and switching or distribute 4 of HDMI output signal. It supports input and output resolution up to UD(4Kx2K@30Hz).

- ✓ Supports input and output resolution UD(4Kx2K)
- ✓ Supports HDCP ON/OFF function, HDCP 1.3Ver
- ✓ Supports EDID WRITE
- ✓ Supports 3D



6X4 UD HDMI SELECTOR SWITCH

MSHM-64A



Specification

Pixel Clock	25MHz ~ 300MHz Digital Video Bandwidth
Input / Output Channel	HDMI Input 6 Channels / HDMI Output 4 Channels
Input/Output Connector	HDMI Type A Connector
HDMI Compliance	HDMI 1.4b Specifications
Audio Sampling Frequency	32KHz, 44.1KHz, 48KHz, 88.2KHz, 96KHz, 176.4KHz, 192KHz
Resolution	<ul style="list-style-type: none">▪ VGA, SVGA, XGA, UXGA for PC▪ 480i/P, 720P, 1080i/P , 4Kx2K for UHDTV
Input/Output Signal	TMDS Signal
Remarks	<ul style="list-style-type: none">▪ 4K x 2K(3840x2160/30Hz) Formats Support▪ 3D Support▪ HDCP On/Off Support, HDCP 1.3Ver Support▪ EDID Write Support
Power Consumption	DC +5V / 3A Adapter
Operating Conditions	<ul style="list-style-type: none">▪ Temperature : 0 ~ 40 °C▪ 80% Humidity, Non-Condensing
Dimension(W x D x H)	188 x 151 x 45 mm, Weight : 1Kg

