

MSMP-2210 Plus

Multimedia Player

IMAGE



DEFINITION

- MSMP-2210 Plus can display Audio, Video and Image format stored in internal HDD Memory through each output port as Digital/Analog signal.
- MSMP-2210 Plus, Multi-Media test device, was designed to test display devices such as Projector, HDTV, PDP, TFT-LCD etc.
- Compare with DVD player, it can especially support both ATSC and DVB format of the Component, DVI, D-Terminal, Analog, HDMI up to 1080i/p, 720p, 576i/p, 480i/p etc.

SPECIFICATION

Output	TV/S-VHS	NTSC, PAL
	Component(Y/Pb/Pr)	480i/p, 576i/p, 720p, 1080i/p
	HDMI	* 1.2 Version
		* CEC Support
		* 480i/p, 576p, 720p, 1080i/p
	Analog(R/G/B)	* 8~230MHz
		* H : 10~120KHz
		* V : 10~120Hz
		* Resolution : 2048X2048
	DVI-D	25~165MHz (Not Supported to HDCP)
	D5	525i/p, 750p, 1125i/p
	Audio	Mono R/L(RCA), SPDIF(Optical), Stereo
Video Format	MPG(MPEG1/2/4), AVI(MPEG1/2/4-V3, DivX3/4/5, Xvid, VC-1, DX50), WMV(WMV9), TP(MPEG Layer), ASF, TS(MPEG Layer), TRP(MPEG Layer) : Up to 1920x1080P/50,60Hz	
Audio Format	MP3, WMA, AAC, PCM, AC3, WAV, BSAC, WMAPRO	
Image Format	JPEG, BMP, PNG, GIF (BMP, PNG : RATIO is not support)	
	* Resolution : 2048x2048	
HDCP Function	Receivable (1.1 Version)	
The Method of Storage	USB 2.0 Device	
HDD Memory	2.5"HDD (80GB)	
Power Consumption	100~240VAC, 50/60Hz Auto Switch	
Operating Conditions	* Temperature : 0~40℃	
	* 80% Humidity, Non-condensing	
Dimension(WXDXH)	400 X 240 X 55mm, Weight : 2.7Kg	

* All specifications are subject to change without any notice.

MSMP-2210 Plus

Multimedia Player

Remote Controller (Optional Product)

- You can use remote box in order to promote work efficiency, before operating remote box, first of all, check baud rate and protocol of communication.



• MSMP-002L

Tel. 82-55-297-8880 / Fax. 82-55-256-7388

Address. #42-20, Palyong, Changwon, Gyeongnam, 641-847, Korea

Homepage. www.Ltdmaster.com

E-mail. sales@Ltdmaster.com / webmaster@Ltdmaster.com

Master Co., Ltd



Find Your Digital Solutions!