

OHS42

4x2 HDMI Select

IMAGE



DEFINITION

- The HDMI Selector, allows four(4) digital videos and digital audio source to share two(2) video display, and can be duplicated on the other HDTV display, which means to support one(1) HDTV connections.
- HDMI ports transmit digital TMDS video signals with encrypted audio.
- For easy switching of digital video and digital audio sources, it offers remote control unit, or a manual switching button place on the unit itself.

SPECIFICATION

Input Channel	4 Channels
Output Channel	2 Channels
Input/Output Connector	HDMI A Type
Frequency Bandwidth	1.65Gbps (Single Link)
Input Signal	HDMI (TMDS) Single Link, 4 Ports
Output Signal	* Digital A/V : HDMI (TMDS) Single Link, 2 Ports * Digital Audio : Optical (Toslink) and COAXIAL, one port each
HDMI Compliance	1.2 Version
HDCP Compliance	1.1 Version
Resolution	* VGA, SVGA, XGA, UXGA, WUXGA for PC * 480i/p, 576i, 720p, 1080i/p for HDTV
Power Consumption	DC+5V, 2A
Operating Conditions	* Temperature : 0°C~50°C * Humidity : 80%, Non-condensing
Dimension(WXDXH)	320 X 165 X 38mm, Weight : 1.1Kg

* All specifications are subject to change without any notice.

Tel. 82-55-297-8880 / Fax. 82-55-256-7388

Address. #42-20, Palyong, Changwon, Gyeongnam, 641-847, Korea

Homepage. www.Ltdmaster.com

E-mail. sales@Ltdmaster.com / webmaster@Ltdmaster.com

Master Co., Ltd



Find Your Digital Solutions!