

MSHM-305A/310A

3x5/3x10 HDMI Distributor

IMAGE



DEFINITION

- 본 기기는 Digital Video Source로부터 3개의 HDMI(High-Definition Multimedia Interface) 입력을 받아 선택된 하나의 디지털 영상 & 오디오를 다수의 HDMI 디스플레이 기기(프로젝터, PDP, HDTV, LCD)에 연결/분배하기 위한 시스템입니다.

SPECIFICATION

Input/Output Channel	* MSHM-305A : 3 Channels / 5 Channels * MSHM-310A : 3 Channels / 10 Channels
Pixel Clock	25~165MHz (TMDS Clock : 25~225MHz)
Input/Output Connector	Type A Connector
HDMI Compliance	HDMI 1.3 Specification
Audio Sampling Frequency	Maximum 192KHz (5 Channels)
Resolution	* VGA, SVGA, XGA, UXGA for PC * 480i/p, 720i/p, 1080i/p for HDTV
Input/Output Signal	TMDS
Options	* Supports HDCP setting * Supports EDID Mode selecting
Power Consumption	AC 100~240VAC, 50/60Hz Auto Switch
Operating Conditions	* Temperature : 0~40℃ * 80% Humidity, Non-condensing
Dimension(WXDXH)	430 X 250 X 55mm, Weight : 3.2Kg

* All specifications are subject to change without any notice.

전화. 055-297-8880 / 팩스. 055-256-7388

주소. 경남 창원시 팔용동 42-20번지 (우641-847)

Homepage. www.Ltdmaster.com

E-mail. sales@Ltdmaster.com / webmaster@Ltdmaster.com

Master Co., Ltd



Find Your Digital Solutions!