

MSMP-2210 Plus

Multimedia Player

IMAGE



DEFINITION

- 본 제품은 HDD 메모리에 저장된 영상패턴, 동영상, 오디오 등의 다양한 A/V 소스를 이용하여 다수의 출력 단자를 통해 디스플레이 장치를 검사 및 테스트하는 기기입니다.
- 기존의 DVD와는 달리 Component와 HDMI 480P, 576P, 720P, 1080i, 1080P등의 ATSC 포맷과 유럽형 DVB Format 출력이 가능하도록 설계되어있어 구주향 및 미주향에 관계없이 다양한 Projector, PDP, LCD의 디스플레이기기 검사에 용이합니다.

SPECIFICATION

Output	TV/S-VHS	NTSC, PAL
	Component(Y/Pb/Pr)	480i/p, 576i/p, 720p, 1080i/p
	HDMI	* 1.2 Version
		* CEC Support
		* 480i/p, 576p, 720p, 1080i/p
	Analog(R/G/B)	* 8~230MHz
		* H : 10~120KHz
		* V : 10~120Hz
* Resolution : 2048X2048		
DVI-D	25~165MHz (Not Supposed to HDCP)	
D5	525i/p, 750p, 1125i/p	
Audio	Mono R/L(RCA), SPDIF(Optical), Stereo	
Video Format	MPG(MPEG1/2/4), AVI(MPEG1/2/4-V3, DivX3/4/5, Xvid, VC-1, DX50), WMV(WMV9), TP(MPEG Layer), ASF, TS(MPEG Layer), TRP(MPEG Layer) : Up to 1920x1080P/50,60Hz	
Audio Format	MP3, WMA, AAC, PCM, AC3, WAV, BSAC, WMAPRO	
Image Format	JPEG, BMP, PNG, GIF (BMP, PNG : RATIO is not support) * Resolution : 2048x2048	
HDCP Function	Receivable (1.1 Version)	
The Method of Storage	USB 2.0 Device	
HDD Memory	2.5"HDD (80GB)	
Power Consumption	100~240VAC, 50/60Hz Auto Switch	
Operating Conditions	* Temperature : 0~40 °C	
	* 80% Humidity, Non-condensing	
Dimension(WXDXH)	400 X 240 X 55mm, Weight : 2.7Kg	

* All specifications are subject to change without any notice.

MSMP-2210 Plus

Multimedia Player

Remote Controller (Optional Product)

- You can use remote box in order to promote work efficiency, before operating remote box, first of all, check baud rate and protocol of communication.



• MSMP-002L

전화. 055-297-8880 / 팩스. 055-256-7388

주소. 경남 창원시 팔용동 42-20번지 (우641-847)

Homepage. www.Ltdmaster.com

E-mail. sales@Ltdmaster.com / webmaster@Ltdmaster.com

Master Co., Ltd



Find Your Digital Solutions!