

MSVD-250N

Analog Distributor

IMAGE



DEFINITION

- 신호원에서 출력되는 표준신호(R, G, B, H-Sync, V-Sync)를 모니터로 분배하여 주는 장비입니다.
- 자동화 생산라인 및 일반 생산라인에서 발생하는 Loss Time을 최소화 함으로써 생산성 향상에 많은 효과를 올릴 수 있고, Display Room과 Show Room 등에도 널리 사용할 수 있습니다.

SPECIFICATION

Input/Output Channel	1 Channel / 5,10,15,20 Channels
H-Sync Bandwidth	10~200KHz
V-Sync Bandwidth	10~200Hz
Pixel Clock	8~250MHz
Input Connector	BNC (R,G,B,HS,VS) & 15P D-Sub
Output Connector	15P D-Sub
Video Level Attenuation	Input(700mV / Load 75ohm)±10mV : Level Control for VR
Sync Output Level	3.0V~5.2V /inherited sync level is 4.8Vp-p
Power Consumption	AC 100~240VAC, 50/60Hz Auto Switch
Operating Conditions	* Temperature : 5~70℃ * 80% Humidity, Non-condensing
Dimension(WXDXH)	* 5,10 Channel : 340 X 219 X 113mm, Weight : 3.2Kg * 15,20 Channel : 340 X 219 X 163mm, Weight : 4.8Kg

* All specifications are subject to change without any notice.

전화. 055-297-8880 / 팩스. 055-256-7388

주소. 경남 창원시 팔용동 42-20번지 (우641-847)

Homepage. www.Ltdmaster.com

E-mail. sales@Ltdmaster.com / webmaster@Ltdmaster.com

Master Co., Ltd



Find Your Digital Solutions!